

Product Specification-- JHD-2A0

| ITEM(項目) | SPECIFICATION(規格) |
|----------------------------------|---|
| LCD Display(尺寸) | 18.5" active matrix TFT LED Panel (16 : 9) |
| *Pixel Pitch(點距) | 0.3(H) x 0.3(V) mm |
| *Max. Resolution(最大解析度) | 1366(H) x 768(V) |
| Display Area(顯示區域) | 409.8 (H) x 230.4 (V) mm |
| Set Diamention(整機尺寸) | 446(H) x 328/285 (V) x 160/55(D) mm (With / Without Base) |
| Package Diamention (包裝大小) | 550 (H) x 355(V) x 112(D) mm |
| *Contrast Ratio(對比度) | 1000:1 (Typical) |
| *Brightness(亮度) | 250 cd/m2 (Typical) |
| *Response Time(反應時間) | 5 mS (Typical) |
| Display Color(顏色) | 16.777 M |
| *View Angle H (視角) V | 170° (Typical) 160° (Typical) |
| TV System(電視系統) | NTSC |
| PC Signal Connector(電腦接頭) | VGA D-sub 15 Pins |
| HDMI | HDMI |
| USB Video(影像) | Support (支援)MJEG, Xvid, MPEG2,MPEG4, H264 |
| Audio (聲音) | Support (支援)MP3, WMA, AAC, MP2, PCM |
| Audio/Video (影音) | AV Input x 1, YPbPr x 1, PC Audio Input x 1 |
| User Control (使用者按鍵) | Power, Source, Menu, CH+, CH- , VL+, VL- |
| AC Power(電源輸入) | AC Input: 100 - 240V , 0.5A 50/60Hz |
| Operating Conditions (動作環境條件) | Temperature(溫度): 0° C - 40° C Humidity(濕度): 10 - 80% |
| Storage Conditions (儲存環境條件) | Temperature(溫度): -20° C - 60° C Humidity(濕度): 5 - 90% |
| Certification(安規認證) | |
| Weight(重量) | Net : 2.42Kg, Gross: 3.02Kg |
| Loading Quantity(裝載量) | 20Ft --- 1324 Sets, 40Ft --- 2640 Sets (without Pallet) |