

產品規格Specification-- JHD-6A1 LED TV/DTV (Special)

ITEM(項目)	SPECIFICATION(規格)
LCD Display(尺寸)	64.53" active matrix TFT LED Panel (16 : 9)
*Pixel Pitch(點距)	2K--0.248(H) x 0.744(V) mm / 4K--0.124(H) x 0.372(V) mm
*Max. Resolution(最大解析度)	2K--1920(H) x 1080(V) / 4K--3840(H) x 2160(V)
Display Area(顯示區域)	1428.48 (H) x 803.52 (V) mm
Set Diamention(整機尺寸)	1456(H) x 910/840(V) x 300/65(D) mm (With有 / Without Base無底座)
Package Diamention (包裝大小)	1570(H) x 960(V) x 185(D) mm
*Contrast Ratio(對比度)	4000:1 (Typical中間值)
*Brightness(亮度)	420 cd/m2 (Typical中間值)
*Response Time(反應時間)	5.5 mS (Typical中間值)
Display Color(顏色)	16.777 M
*View Angle H (視角) V	178° (Typical中間值) 178° (Typical中間值)
TV System(電視系統)	NTSC TV & DTV(數位電視)
PC Signal Connector(電腦接頭)	VGA D-sub 15 Pins
HDMI	HDMI x 2
USB x 2 Video(影像) Photo (圖片)	Support (支援) DIVX, MPEG-1, MPEG-2, MPEG-3, WVC, AVS, WMV3, H263, H264, H265 Support (支援)JPEG, PNG, BMP, MPO
Audio/Video (影音)	AV Input x 2, Audio Output x 1, YPbPr x 1, PC Audio Input x 1,
User Control (使用者按鍵)	Power, Source, Menu, CH+, CH- , VL+, VL-.
AC Power(電源輸入)	AC Input: 100 - 240V , 3.0A 50/60Hz
**INTERNET(網路)	有線及無線網路(DDR1.5G , 儲存空間8G)
Base(底座)	1100(W) x 70(H) x 300 (D) mm
Wall Mount(壁掛孔距)	40(W) x 20(H) mm
Operating Conditions (動作環境條件)	Temperature(溫度): 0° C - 40° C Humidity(濕度): 10 - 80%
Storage Conditions (儲存環境條件)	Temperature(溫度): -20° C - 60° C Humidity(濕度): 5 - 90%
Certification(安規認證)	
Weight(重量)	Net : Kg, Gross: Kg
Loading Quantity(裝載量)	20Ft --- 78 Sets, 40Ft --- 196 Sets (without Pallet無棧板)

*規格由LED Panel決定，Panel不同規格會隨著變動。

**機種分類：A--2K，D--2K數位電視，H--4K(無VGA端子)，S--4K聯網(無VGA端子)。